

ELEPHANT SNOT®



Reg. No. ECP 02007

Graffiti Solutions

www.graffitisolutions.com

1.800.891.0091

G R A F F I T I R E M O V E R

GENERAL DESCRIPTION

ELEPHANT SNOT® Graffiti Remover is one of five "Graffiti Max" products, each custom formulated for specific graffiti removal needs.

ELEPHANT SNOT® Graffiti Remover is the right choice for the job if it is a "porous surface" such as the following.

RECOMMENDED FOR REMOVAL ON

Brick, mortar, masonry, cement, concrete, stucco, landscaping pavers, terrazzo. Natural stone surfaces such as granite, marble, sandstone, porous rocks, both rough and polished. Also effective on: glass, ceramic, porcelain, glazed tile, porous tile, grout.

PRODUCT FEATURES AND BENEFITS

- **Non-drip** formula for easy application without messy runs and drips.
- **Fast removals** - clings to the surface for maximum penetration and maximum speed of removal.
- **Low odor** with minimum or no ventilation requirement for added safety, indoor or out.
- **Nonflammable**, noncombustible, minimal fire hazard formula.
- **All temperature** effective removals from below freezing cold (24°F) to "very hot" (90°F+) conditions.

SAFETY INSTRUCTIONS FOR USE

- **Always wear protective eye wear and chemical resistant gloves. Can cause burns.**
- Protect all exposed skin areas with chemical resistant covering.
- If product gets on skin, wash off immediately. If product gets in eyes, flush with water for 15 minutes.
- **FOR PROFESSIONAL USE ONLY.**

GENERAL INSTRUCTIONS FOR USE

- Stir before use.
- Apply directly by brush or roller.
- Allow to penetrate affected area for 15-20 minutes (30-40 minutes cold temperatures.)
- Use power washer with 15° tip with 1000 - 3000 PSI maximum pressure. For optimum performance and speed of removal use hot water (190°F). Excellent results may be obtained with a Cold Water Power Washer with the above specifications by doubling the dwell time (30-40 minutes).
- Alternative Method: Allow to penetrate for 30-35 minutes, agitate with stiff brush, and remove with water hose at maximum nozzle pressure.
- Repeat process if necessary.
- Use **SHADOW MAX** to remove any ghosting or shadow.
- Clean up all equipment after each use with water.

SPEC'S - GENERAL PROPERTIES

CONSISTENCY

No drip gel clings to vertical surfaces without dripping.

COVERAGE

100 to 200 Sq. ft./gal. depending on porosity of surface.

TEMPERATURE USAGE

Not limited, will work slower at cold temperatures.

STORAGE

Stores between 40°F and 130°F. DO NOT FREEZE. If frozen, thaw and remix before using. Keep out of the reach of children.

FLAMMABILITY

Nonflammable, noncombustible. Flash point over 200°F.

V.O.C.S

.4 lbs/gallon, 50 grams/liter. H.A.P.S. - none.

BIODEGRADABLE

Yes

VOLATILITY

Very low rate of evaporation. No ventilation required unless used in a confined space.

SHIPPING

Not regulated, D.O.T. Proper shipping name: Cleaning Compound N.O.S., Class 55.

EFFECTIVE ON THE FOLLOWING

Paint spills on floors, spray booth over sprays, even many difficult to remove 2-part paints, epoxies, urethanes, can be removed effectively with **ELEPHANT SNOT®**.

TEST FIRST

ELEPHANT SNOT® should not be used for any other purpose/removal, without thoroughly testing in an inconspicuous area for effect.

NOTE: If removing "shadows or ghosts" from any of the above surfaces we recommend the use of **SHADOW MAX** Graffiti Remover for maximum effectiveness.

For removals from all types of metals, "durable" baked on painted surfaces such as auto, bus, truck, other factory applied paints, or fiberglass, use our **SMOOTH MAX** Graffiti Remover.