



*"When channelization is used to delineate a pedestrian pathway, a continuous detectable edging should be provided throughout the length of the facility such that pedestrians using a long cane can follow it. These detectable edgings should comply with the provisions of Section 6M.04."*

**- MUTCD 11th Edition**

**3M** We use 3M  
Reflective  
Sheeting.

Part of the RightPath line of ADA products

# SAFETYRAIL™

Pedestrian Barricade



## SAFETYRAIL™ FEATURES:

SafetyRail is a continuous, interlocking device designed for creating accessible work zones. This device adheres to ADA guidelines and MUTCD 2009 Edition Standards as a sidewalk closure barricade and longitudinal channelizer.

SafetyRail is designed for use with PSS Wave® Guide Rail. The upper Wave Guide Rail is smooth, continuous, and safe for trailing of the hand. The lower Wave Guide Rail measures 1.5" from the ground, reducing potential for trapped cane tips. Wave "notch" design keeps guide rails securely in bushings.

Patents: <http://bit.ly/3cHVTp8>



## SAFETYRAIL FEATURES:

**Dimensions:** 3.25" W x 38" H x 24" L at base

**Weight:** 7 lbs empty or up to 25 lbs with sand

**Material:** High-density polyethylene plastic, UV inhibitors

**MASH Eligibility:** SafetyRail: WZ-359

**Wave Guide Rail:** 0.8" x 7.5" x 48" or 72"  
High-density polyethylene plastic, UV inhibitors

## PSS WAVE GUIDE RAIL:

Available in four-foot or six-foot lengths. Encapsulated ends eliminate cane or hand snagging hazards.

Retroreflective sheeting meets all state and federal specifications and is available in Engineer, Hi-Intensity, and Diamond grades. Wave accepts sheeting on one or both sides.

